

1. A transmit power control method in a CDMA mobile communication system comprising:

5 a calculating step of, when a result of the checking step shows
that two or more BTSs are connected, selecting CH receive SIRs
(Signal to Interference Ratios) corresponding to the connected BTSs,
and making a calculation by using the selected values;

an upper limit setting step of, when the result of the checking step shows that only one BTS is connected, setting the reference value Sref to an upper limit; and

wherein it is possible to decide the reference value S_{ref} in response to a variation in selection/synthesis gain due to an increase or a decrease of the number of connected BTSs.

3. A transmit power control method in a CDMA mobile communication system comprising:

5 a calculating step of, when a result of the checking step shows

10 a reference value Sref according to a result of calculation;

15 a reporting step of reporting the changed reference value S_{ref} to all the connected BTSs in each of the steps, wherein it is possible to decide the reference value S_{ref} in response to a variation in selection/synthesis gain due to an increase or a decrease of the number of connected BTSs;

said the calculation made by using the selected value in the calculating step comprises:

any one of the step of calculating a difference (X) between the Smax and the Sscd and the step of calculating the number (Nbts) of
30 BTSs in which a difference between the Smax and the receive SIR becomes a predetermined value T2 or less.

4. A transmit power control method in a CDMA mobile communication system according to claim 3, wherein, when the X is equal to a predetermined threshold value T1 or more, it is decided

5

5

5

where γ is a desired constant,

Sref0 is an upper limit.

5

a calculating step of, when a result of the checking step shows that two or more BTSs are connected, selecting CH receive SIRs (Signal to Interference Ratios) corresponding to the connected BTSs, and making a calculation by using the selected values;

10

an upper limit setting step of, when the result of the checking

step shows that only one BTS is connected, setting the reference value Sref to an upper limit;

15 a reporting step of reporting the changed reference value Sref to all the connected BTSs in each of the steps, wherein it is possible to decide the reference value Sref in response to a variation in selection/synthesis gain due to an increase or a decrease of the number of connected BTSs;

20 said CH receive SIR is any one of a Perch CH receive SIR and a communication CH receive SIR for each of the connected BTSs;

said the calculation made by using the selected value in the calculating step comprises:

25 any one of the step of selecting the maximum value Smax and the second largest value Sscd from among the CH receive SIRs corresponding to the connected BTSs and the step of selecting the maximum value Smax from among the CH receive SIRs corresponding to the connected BTSs; and

30 any one of the step of calculating a difference (X) between the Smax and the Sscd and the step of calculating the number (Nbts) of BTSs in which a difference between the Smax and the receive SIR becomes a predetermined value T2 or less, and

35 said reference value changing step is any one of the step of changing the reference value Sref to a value according to the difference (X) and the step of changing the reference value Sref to a value according to the number (Nbts).

8. A transmit power control method in a CDMA mobile communication system according to claim 7, wherein, when the X is equal to a predetermined threshold value T1 or more, it is decided that only a small gain can be obtained by selection/synthesis, thereby
5 setting the reference value Sref to an upper limit irrespective of

096306278-1000000

9. A transmit power control method in a CDMA mobile communication system according to claim 7, wherein, when the X is equal to a predetermined threshold value T1 or less, it is decided that a sufficient gain can be obtained by selection/synthesis, thereby setting the reference value Sref to a value according to the X.

10. A transmit power control method in a CDMA mobile communication system according to claim 7, wherein the reference value Sref is found by the following expression:

5 $S_{ref} = S_{ref0} - (T1 - X) \times$
 where is a desired constant,
 $T1$ is a predetermined threshold value, and
 S_{ref0} is an upper limit.